


- SPECS:**
1. MATERIAL:- 1.6 THK CORROSION RESISTANT 304L2 EPOXY POWDER COATED
 2. GALVANIZED DOUBLE INLET VARIABLE SPEED CONTROLLED FAN 220 VOLT, 5.8 Amps MAX, 0.55 KW
 3. SIDE ACCESS WASHABLE PRE-FILTER CAPABLE OF UP TO 250Pa WITH 200g DUST HOLDING CAPACITY
 4. SIDE ACCESS SECONDARY POCKET FILTER 90% CAPABLE OF UP TO 250Pa WITH 300g DUST HOLDING CAPACITY
 5. MODULAR UNITS EASILY ROTATED THROUGH 90° INCREMENTS
 6. FAN CAN BE THERMOSTATICALLY CONTROLLED TO RUN BETWEEN CERTAIN TEMPERATURES
 7. VOLUME OF AIR SUPPLIED BY FAN IN THIS CONFIGURATION IS BETWEEN 0 AND 10 M³/Sec

PAINING OYSTER WHITE STRUCTURE POWDER COAT

Quantity	1	MATERIAL :- 1.6 THK MS	APPROX. WEIGHT -	100 Kg
DESIGNED BY	CHECKED BY	APPROVED BY	DATE	SCALE
 <p>MANUFACTURERS OF WASTE REMOVAL AND FILTRATION EQUIPMENT</p> <p>Tel: 031 824 4855 PO BOX 32095 Fax: 086 541 0699 GLENASHLEY 4022</p>		GA OF TYPICAL 3600 MODULAR SIDE ACCESS FILTER UNIT DRAWING No: SS - 0168		
TOLERANCES: + 0.5 - 0.5			12-5-2014	1:1
SHEET				