



- SPECS:**
1. MATERIAL:- 1.6 THK CORROSION RESISTANT 3CR12 EPOXY POWDER COATED
 2. GALVANIZED DOUBLE INLET VARIABLE SPEED CONTROLLED FAN 220 Volt, 0.8 Amps MAX, 0.2 kW
 3. SIDE ACCESS WASHABLE PRE-FILTER CAPABLE OF UP TO 250Pa with 200g DUST HOLDING CAPACITY
 4. SIDE ACCESS SECONDARY POCKET FILTER 90% CAPABLE OF UP TO 250Pa with 300g DUST HOLDING CAPACITY
 5. MODULAR UNITS EASILY ROTATED THROUGH 90° INCREMENTS
 6. FAN CAN BE THERMOSTATICALLY CONTROLLED TO RUN BETWEEN CERTAIN TEMPERATURES
 7. VOLUME OF AIR SUPPLIED BY FAN IN THIS CONFIGURATION IS BETWEEN 0 AND 0.15 M³/Sec

PAINTING: OYSTER WHITE STRUCTURE POWDER COAT

RevNo	Revision note	Date	Signature	Checked

Quantity	1	MATERIAL :- 1.6 THK MS	APPROX. WEIGHT -	50 Kg
DESIGNED BY	CHECKED BY	APPROVED BY	DATE	SCALE
MANUFACTURERS OF WASTE REMOVAL AND FILTRATION EQUIPMENT		GA OF TYPICAL 3300 SIDE ACCESS FILTER UNIT		
STERISAN PVT. LTD.		DRAWING No:	SS - 0089	SHEET